5MP Pan-Tilt-Zoom Camera with 42x Optical Zoom





Matrix has introduced Pan Tilt Zoom (PTZ) Cameras that are designed for all round surveillance. A PTZ Camera works by moving the camera in different directions (Pan and Tilt) to get the whole picture of the surveillance area and zooming in for further details of the security events. The Pan, Tilt, and Zoom mechanism of PTZ cameras allow it to monitor large areas with greater details. Furthermore, the camera is powered by True WDR algorithm, which ensures evenly balanced images even in varying lighting conditions. The camera is loaded with smart monitoring features like moving to a particular preset position and easy integration through ONVIF making it an ideal product for maximum protection at minimal cost.





True WDR



H.265 Compression



42x Optical Zoom



Upto 256GB In-built Storage



300m IR Range



Low-Light Performance



Intelligent Video Analytics



300 Presets

CERTIFICATIONS









5MP Pan-Tilt-Zoom Camera with 42x Optical Zoom



TECHNICAL SPECIFICATIONS		
CAMERA		
Image Sensor	1/ 2.8" CMOS	
Signal System	PAL/ NTSC	
Minimum Illumination	Color:0.005Lux@F1.2, 0.008, Lux@F1.8, Black and White: 0 lux with IR on	
Shutter Speed	1s - 1/100000s	
Day and Night	IR Cut Filter with Auto Switch	
Wide Dynamic Range	140dB	
Optical Zoom	42x	
Digital Zoom	16x	
LENS		
Focal Length	0.008Lux@F1.8	
Zoom Speed	Approx 7s (Wide-Tele)	
Angle of View	Horizontal:43°-2°	
	Vertical:33°-2° Diagonal:53°-2°	
Aperture Range	F1.8-F6.5	
PAN & TILT		
Pan Range	360° endless	
Pan Speed	Pan Manual Speed: 0.1°~400°/s, Pan Preset Speed: 400°/s	
Tilt Range	0°~90°(Auto Flip)	
Tilt Speed	Tilt Manual Speed: 0.1°~320°/s, Tilt Preset Speed: 320°/s	
3D Position	Yes	
Presets	300	
Scan	8	
Cruise	8, up to 48 preset per cruise	
Pattern	4	
Power Off Memory	Yes	
ILLUMINATOR		
IR LED	5	
IR Range	Up to 300m	
IR irradiance Angle	Auto/Manual	
COMPRESSION STANDARD		
Video Compression	H.265+/H.265(HEVC)/H.264+/H.264/MJPEG	
Video Bitrate	16Kbps~16Mbps (CBR/VBR Adjustable)	
Audio Compression	G.711/AAC/G.722/G.726	
Audio Bitrate	16~256kbps	

5MP Pan-Tilt-Zoom Camera with 42x Optical Zoom



IMAGE		
Max Resolution	2592x1944	
Mainstream	PAL: 50fps@(1920x1080, 1280x960, 1280x720, 704x576) NTSC: 60fps@(1920x1080,1280x960,1280x720,704x576)	
Sub Stream	PAL: 25fps@(704x576, 640x480, 352x288, 320x240, 320x192, 320x180) NTSC: 30fps@(704x576, 640x480, 352x288, 320x240, 320x192, 320x180)	
Third Stream	PAL:25fps@(1920x1080,1280x720,704x576,640x480,320x240, 320x180) NTSC:30fps@(1920x1080, 1280x720, 704x576, 640x480, 640x360, 320x240, 320x192, 320x180	
Image Setting	Brightness, Contrast, Saturation/Sharpness	
Image Enhancement	BLC, HLC, 2D DNR, 3D DNR, AWB, EIS, IP Address Filtering, AGC, Anti- flicker, Corridor Mode, Deblur, Watermark	
ROI	Up to 8 areas	
OSD	16x16, 24x24, 32x32, 48x48, 64x64, 96x96. Total 5 Regions	
Picture Overlay	Yes	
Privacy Mask	Up to 28 areas (24 mask areas and 4 mosaic areas)	
Smart Defog	Yes	
FEATURE		
Alarm Trigger	Motion Detection, Network Disconnection, External Input, Audio Alarm	
Video Analytics	Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Object Left, Object Removed	
	NETWORK	
Protocol	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL	
System Compatibility	ONVIF S,G,Q & T Ready	
INTERFACE		
Communication Interface	1RJ45 10/100 self-adaptive Ethernet Port	
Audio	1/1	
Alarm	4/2	
Reset Button	Yes	
On-Board Storage	Built-in Micro SD card slot up to 256GB	
GENERAL		
Web Page Language	Up to 15 Languages	
Operating Conditions	Temperature: -40°C~60°C / Humidity: 0~90%(non-condensing)	
Power Supply	PoE (802.3at) / AC 24V	
Power Consumption	12W MAX / 25W MAX (With IR on)	
Protection	IP66	
Heater	N/A	
Dimension	Ф205mmX308mm	
Weight	4 Kg	

5MP Pan-Tilt-Zoom Camera with 42x Optical Zoom



Note: Specifications are subject to change without prior notice

ABOUT MATRIX

Established in 1991, Matrix is a leader in security and telecom solutions for modern businesses and enterprises. Matrix, an innovative, technology-driven, and customer-focused organization, is committed to keeping pace with the revolutions in the security and telecom industries. With more than 40% of its human resources dedicated to the development of new products, Matrix has launched cutting-edge products such as Unified Communications, IP-PBX, Universal Gateways, Convergence, VOIP Gateways, and GSM Gateways, IP Video Surveillance, Access Control, and Time-Attendance. These solutions are feature-rich, reliable, and conform to international standards. Having global footprints in Europe, North America, South America, Africa, and Asia through an extensive network of more than 1000 system integrators, Matrix ensures that the products serve the needs of its customers faster and longer. Matrix has gained the trust and admiration of customers representing the entire spectrum of industries. Matrix has won many national and international awards for its innovative products.



MATRIX COMSEC

Head Office 394-GIDC, Makarpura, Vadodara-390 010, India. Ph: +91 265 613 7222

E-mail: Inquiry@MatrixComSec.com

Factory 19-GIDC, Waghodia, Dist. Vadodara-391 760, India. Ph: +91 265 613 7222

MATRIX COMSEC – North America 2 Wickstead Crt, Brampton, Ontario, L6R1N8

Ph: (+1) 408-643-0581 (USA) Ph: (+1) 437-266-1005 (Canada)

www.MatrixVideoSurveillance.com

5MP Pan-Tilt-Zoom Camera with 42x Optical Zoom

