COSEC ARGO FACEE

Redefining Facial Recognition Technology



CREDENTIAL SUPPORT

Human Face Yes
PIN Yes
Card EM Prox
BLE - Mobile Yes

CAPACITY

User Profiles50,000Face Templates200,000Max. Templates Per User30Event Logs500,000

Face Recognition

Algorithm Deep Learning based Face Recognition

Fake Face Detection Yes

Face Identification 1:200,000 in < 1 sec

1:1 in < 0.5 sec

Face Enrolment Face Recognition Terminal

Enrolment Station Upload Images Exception Faces

GENERAL SPECIFICATIONS

Dimensions (HxWxD) 186mm x 74 mm x 50mm

(7.3" x 3" x 2 ")

Weight 650gms (1.433 lbs)

Display 3.5" IPS LCD (Touch Screen)

Display Resolution480 x 320 PixelGorilla GlassYes (Gorilla Glass 3)

CPU Quad Core ARM Cortex-A7 @ 1.5 GHz

GPU Built-in 2 TOPS Neural Network Computing Performance

RAM 2 GB DDR4 Flash Memory 16 GB eMMC

SD Card No (Built-in 16GB eMMC provided)

Tamper Detection Yes

BuzzerYesIR LEDsYesIngress ProtectionIP65Ingress ProtectionIK06

Certificate CE, FCC, BIS, UL, RoHS

Operating Temperature 0°C to 50°C **Storage Temperature** -20°C to 60°C

Humidity 5% to 95 % RH Non-Condensing

CAMERA

RGB Camera2MP Surveillance Grade, IR BlockedInfrared Camera2MP Surveillance Grade, IR Band Pass

Camera Sensors SONY IMX 307, EXMOR Technology, STARVIS Series

COMMUNICATION

Ethernet Yes (10/100 Mbps - 1 port)

 PoE
 Yes (IEEE 802.3 af)

 WiFi
 Yes (802.11 b/g/n)

3G/4G/LTE Yes (Additional USB Modem) **BLE** Yes (Version4.2) (8m Range)

USB Yes (USB 2.0)

Micro USB-Type B

INTERFACE

Exit Switch Interface Yes

External Reader Support Yes (MATRIX and 3rd Party)

External Reader Interface

RS232Wiegand

Power

• 12VDC @ 0.5A

■ Allowed - GREEN LED

• Buzzer

Wiegand Yes (Selectable IN/OUT)

IN: 26 Bit format OUT: Configurable

Door Lock Relay Yes (30VDC @ 2A, Dry Contacts NO/NC/COM)

Door Lock Power Internal PoE Power: 12VDC @ 0.250 A

Internal Adapter Power 12VDC @ 0.5 A

External Power 12VDC @ 2A

INSTALATION

Wall Mount Yes - Plastic Back Cover with Screws
Flush Mount Yes - Metal Bracket with Screws

ACCESSORIES

Power Adapter 12VDC @ 2A (CE, FCC, UL, BIS)

ABOUT MATRIX

Established in 1991, Matrix is a leader in Security and Telecom solutions for modern businesses and enterprises. An innovative, technology driven and customer focused organization the company is committed to keep pace with the revolutions in the Security and Telecom industries. With around 40% of its human resources dedicated to the development of new products, Matrix has launched cutting-edge products like Video Surveillance Systems - Video Management Software, Network Video Recorder and IP Camera, Access Control and Time-Attendance Systems as well as Telecom Solutions such as Unified Communications, IP-PBX, Universal Gateways, VoIP and GSM Gateways and Communication Endpoints. These solutions are feature-rich, reliable and conform to the international standards. Having global footprints in Asia, Europe, North America, South America and Africa through an extensive network of more than 2,500 channel partners, Matrix ensures that the products serve the needs of its customers faster and longer. Matrix has gained trust and admiration customers representing the entire spectrum of industries. Matrix has won many international awards for its innovative products.



MATRIX COMSEC

Head Office

394-GIDC, Makarpura, Vadodara-390 010, India.

Ph: (+91) 265-613-7222

E-mail: lnquiry@MatrixComSec.com

Factory

19-GIDC, Waghodia, Dist. Vadodara-391 760, India.

Ph: (+91) 265-613-7222

MATRIX COMSEC - North America

2 Wickstead Crt, Brampton, Ontario, L6R 1N8. +1 408-643-0581 (USA) +1 437-266-1005 (Canada)

www.MatrixAccessControl.com